

HABEGGER HIT-16

The professional wire rope hoist with a range of uses. Powerful yet compact.



Technical Data	HIT-16
Rated force (pulling, lifting, lowering)	1600 kg
Overload protection at	2400 kg
Weight without rope	12 kg
Rope diameter	11,2 mm
Effective rope breaking load	8000 kg
Rope feed per double stroke	60 mm
Load on lever at rated load	35 kg

Basic equipment	Article no.
Unit with lever tube, 20 m rope	00800
Complete with storage case and 2 m strap	00798
Unit with lever tube without rope	00799
Dimensions LxWxH	300x547x120 mm

Wire rope configured

with thimble, an eyelet hook and locking bar on one end and a pointed end on the other.
Other lengths and configurations on request.

- Light alloy housing
- Anchorage bolts secured
- Overload protection by shear pin
- Exchangeable shear pins in handle
- Expansion for hydraulic drive
- With handle
- Lever tube can be pulled out
- Storage case available

Wire ropes on reel

Diameter Weight	11,2 mm 0,41 kg/m
Length in m	Article no.
10	01111
15	01112
20	01113
25	01114
30	01121
40	01122
50	01123
60	01124
70	01131
80	01132
90	01133
100	01134

Wire ropes without reel

Length in m	Article no.
5	01101
10	01102
15	01103
20	01104