

HABEGGER HIT-32

The powerhouse of the manual wire rope hoists. Pulling force in excess of 3 tonnes.

Technical Data	HIT-32
Rated force (pulling, lifting, lowering)	3200 kg
Overload protection at	4800 kg
Weight without rope	21,5 kg
Rope diameter	16,2 mm
Effective rope breaking load	16000 kg
Rope feed per double stroke	30 mm
Load on lever at rated load	50 kg

Basic equipment	Article no.
Unit with lever tube, 10 m rope	00900
Complete with storage case and 2 m strap	00898
Unit with lever tube without rope	00899
Dimensions LxWxH	330x683x148 mm



Wire rope configured

with thimble, an eyelet hook and locking bar on one end and a pointed end on the other.
Other lengths and configurations on request.

- Light alloy housing
- Anchorage bolts secured
- Overload protection by shear pin
- Exchangeable shear pins in handle
- Expansion for hydraulic drive
- With handle
- Lever tube can be pulled out
- Storage case available

Wire ropes on reel

Diameter	16,2 mm
Weight	0,86 kg/m
Length in m	Article no.
10	01221
15	01222
20	01223
25	01224
30	01231
40	01232
50	01233
60	01241
70	01242
80	01243
90	01244
100	01245

Wire ropes without reel

Length in m	Article no.
5	01201
10	01202
15	01203
20	01204